

50th year

DATASHEET



D SERIES

MODULAR SYSTEM

POWER DISTRIBUTION

INDOOR

CRS

DATASHEET

D SERIES

yespan®

MODULAR SYSTEM

POWER DISTRIBUTION

INDOOR

CRS



DIMENSIONS

WIDTH mm	HEIGHT mm	DEPTH mm
400	1400	300
500	1600	400
600	1800	500
700	2000	600
800		
1000		
1200		

MATERIAL DETAILS	THICKNESS	MATERIAL	COATING
Enclosure Frame	1,50 mm	275 gr/m ² Galvanized CRS	Unpainted
Door	1,50 mm	CRS	7035
Side/Back Wall	1,00 mm	CRS	7035
Bottom Plate	1,50 mm	275 gr/m ² Galvanized CRS	Unpainted
Plinth Cover	2,00 mm	CRS	U740V8B
Plinth Corner	2,00 mm	275 gr/m ² Galvanized CRS	Unpainted
Cover Plates	1,00 mm	CRS	7035

DATASHEET

D SERIES



MODULAR SYSTEM

POWER DISTRIBUTION

INDOOR

CRS

SURFACE TREATMENT

: Nanoceramic coating

COATING

: Ral 7035 wrinkle UV resistive polyester powder coating

LOCK

: Poliamide handle with key, 4 points latch

HINGES

: Hidden hinges, zinc coated.
130° opening angle

INSETS

: Door earthing cable (1 piece for each door)

GTIP CODE

: 8538.10.00.00.00

CERTIFICATES

: EAC Certificate
RED Certificate

DECLARATIONS

: CE Declaration of Conformity

YESPAN ELEKTRİK SANAYİ VE TİCARET LTD. ŞTİ.

Head Office : Umurlu mahallesi Aydın OSB 2.Cadde No:41 09630 Efeler / AYDIN - TÜRKİYE
Phone : +90.256. 211 56 56 pbx • info@yespan.com

Branch : Perpa Ticaret Merkezi A Blok Kat: 11 No: 1667 Şişli / İSTANBUL - TÜRKİYE

