

50th year

DATASHEET



H SERIES

MODULAR SYSTEM

CONTROL&PROTECTION

OUTDOOR

CRS

DATASHEET

H SERIES

yespan®

MODULAR SYSTEM

CONTROL&PROTECTION

OUTDOOR

CRS



DIMENSIONS

WIDTH mm	HEIGHT mm	DEPTH mm
800	2000	600
1000	2100	800
1200	2200	

MATERIAL DETAILS	THICKNESS	MATERIAL	COATING
Enclosure Frame	2,50 mm	275 gr/m ² Galvanized CRS	7035
Door	2,50 mm	275 gr/m ² Galvanized CRS	7035
Back Wall	2,50 mm	275 gr/m ² Galvanized CRS	7035
Bottom Plate	2,50 mm	275 gr/m ² Galvanized CRS	7035
Plinth Cover	2,50 mm	275 gr/m ² Galvanized CRS	9005
Plinth Corner	3,00 mm	275 gr/m ² Galvanized CRS	9005
Canopy	2,50 mm	275 gr/m ² Galvanized CRS	7035
Back Mounting Plate	2,50 mm	275 gr/m ² Galvanized CRS	Unpainted

OPTIONAL DETAILS	THICKNESS	MATERIAL	COATING
Side Mounting Plate	2,50 mm	275 gr/m ² Galvanized CRS	Unpainted
19" Swing Frame	2,50 mm	275 gr/m ² Galvanized CRS	7035
19" Fixed Frame	2,50 mm	275 gr/m ² Galvanized CRS	7035
19" Cover Plates	2,00 mm	275 gr/m ² Galvanized CRS	7035
Front Mounting Plate	2,00 mm	275 gr/m ² Galvanized CRS	7035

DATASHEET

H SERIES

yespan®

MODULAR SYSTEM

CONTROL&PROTECTION

OUTDOOR

CRS

PROTECTION CLASS

: IP65

IK CODE

: IK10

SURFACE TREATMENT

: Nanoceramic coating

COATING

: Ral 7035 wrinkle UV resistive polyester powder coating

LOCK

: Polyamide handle with key, 3 points latch

HINGES

: Hidden hinges, stainless steel
130° opening angle

INSETS

: Door earthing cable (1 piece for each door)

GTIP CODE

: 8538.10.00.00.00

CERTIFICATES

: IEC 62208
IP65 Test
IK10 Test
IEC 60068 Seismic Test Zone 4
GR63 Core Seismic Test
ASTM 4169 Transportation Test
Wind Resistance Test
EAC Certificate
RED Certificate

DECLARATIONS

: CE Declaration of Conformity

YESPAN ELEKTRİK SANAYİ VE TİCARET LTD. ŞTİ.

Head Office : Umurlu mahallesi Aydın OSB 2.Cadde No:41 09630 Efeler / AYDIN - TÜRKİYE
Phone : +90.256. 211 56 56 pbx • info@yespan.com

Branch : Perpa Ticaret Merkezi A Blok Kat: 11 No: 1667 Şişli / İSTANBUL - TÜRKİYE

